KODAK EASYSHARE V803 Zoom Digital Camera

Undeniably you.

8.0 MP for prints up to 30 × 40 in. (76 × 102 cm) 3X optical zoom lens Customize with on-camera settings, including the Favorites feature Available in many fresh colors KODAK PERFECT TOUCH Technology Digital Image Stabilization using anti-blur mode
{jumi [hiqmf/jumi_forms.php] [hiqmf/content_camera.html] [100%] [70] [no]} Specifications

Standard featuresSensor type 1/1.8 in. CCDCCD total pixels 8.32 MP (3350 × 2483)Effective pixels 8.0 MP (3273 × 2457)Lens 36–108 mm (35 mm equiv.) f/2.8–4.9Zoom 3X optical, 4X digital, total zoom range 12X
Shutter speed 8–1/2000 sec.LCD 2.5 in. (6.4 cm), 154K pixelsStorage 32 MB internal memory* available, SD/MMC card expansion slot Auto focusType TTL-AFModes normal, macro, infinityFocus range normal wide: 2 ft (0.6 m)–infinity
normal tele: 2 ft (0.6 m)–infinity
macro wide: 2.4 in.–2.3 ft (6–70 cm)
macro tele: 1.3 ft–2.3 ft (40–70 cm)
landscape: 32.8 ft (10.0 m)–infinity
Focus single, continuousAuto focus zones TTL multi-zone (5 zone), center zoneAF assist light yesExposure controlISO sensitivity auto: 80–160
manual: 80, 100, 200, 400, 800, 1600 selectable
Metering modes TTL metering; multi-pattern, center-weighted, center spot Compensation ±2.0 EV with 0.3 EV stepsAE lock when shutter button pressed halfwayHistogram display display on live view and reviewWhite balance auto, daylight, tungsten, fluorescent, open shadeFlashRange 2.0–9.8 ft (0.6–3.0 m) at wide, ISO 140
2.0–6.6 ft (0.6–2.0 m) at tele, ISO 200
Modes auto, fill, off, red eyeShooting specificationsDrive modes single shot, self-timer: 2 and 10 sec., 2-shot self-timer: 10 and 18 sec.
delay shutter (2 sec.)
burst (1 fps up to 4 frames)
Shooting modes auto, SCN (scene mode)Scene modes portrait, sport, landscape, close up, night portrait, night landscape, snow, beach, text/document, fireworks, flower, museum/manner, self-portrait, high ISO, children, backlight, panning, candlelight, sunset, custom, panorama, anti blurClick to capture < 0.4 sec.Shot to shot < 1.2 sec. Still captureStill format JPEG/EXIF v2.21Picture size 8.0 MP (3264 × 2448)
7.0 MP (3264 × 2176)
4.9 MP (2560 × 1920)
3.1 MP (2048 × 1536)
2.5 MP (1920 × 1280)
2.1 MP (1920 × 1080)
1.2 MP (1280x960)
Compression JPEG standardColor modes high color, natural color (default), low color, sepia, black and whiteSharpness sharp, normal, softLong time exposure 0.5–8.0 sec. Review options select all, view by, album, slide show, multi-up, copy, protect, image storage, set up menuEditing crop, KODAK PERFECT TOUCH TechnologyVideo captureFormat QUICKTIME MPEG 4 with audio recording and playbackQuality VGA (640 × 480) at 30 fps, QVGA (320 × 240) at 30 fpsLength continuous based on memory capacityReview options play, rewind, pause, fast forward, stop, forward and rewind by frame, multi-up, multi-select, volume controlEditing trim, make picture from video (1, 4, 9, 16-up), bookmarkingCustomizationCustom settings camera sounds, sound volume, digital zoom, LCD brightness, LCD auto dimmer, auto power off, date/time, video out, photoframe, red-eye pre-flash, date stamp, video date display, blur warning, languageFavoritesFavorites slide show, multi-up, remove Favorites, set-up menuPhysical specificationsI/O interface A/V output (NTSC or PAL, user-selectable), KODAK Camera Dock/Printer Dock Interface, digital (USB 2.0) connectionPower KODAK Li-Ion Rechargeable Digital Camera Battery KLIC-7003, 5V AC adapter, optional KODAK EASYSHARE DocksDedicated buttons shutter, auto/SCN, Favorites, movie, power, flash, zoom, menu, review, Share, delete, five-way switch for navigationTripod mount ¼ in. standardDimensions W × H × D: 4.1 × 2.1 × 1.0 in. (103 × 54.5 × 25 mm
Weight 5.0 oz (141.5 g)
CompatibilityDock compatibility See the Dock Compatibility ChartDirect printing KODAK EASYSHARE Photo Printer 500, IMAGELINK print system compatible, PictBridge-enabledSoftware works with KODAK EASYSHARE SoftwareWarrantyone year